

WINDOW & DOOR APPLICATIONS

SEALANTS							
Product Name	Base	Colour	Skin Formation Time	Tensile Strength	Elongation at Break	Shore A Hardness	Remark
BOSS® 396	Silicone	Clear, black, white	5-10 mins	0.8-1.2 N/mm²	>350 %	26-34	Low odour, non-corrosive to metal
BOSS® 354	Acrylic	White	5-10 mins	----	----	----	Can be painted over after curing
BOSS® 386	Acrylic	Brown, light brown & antares grey	5-10 mins	----	----	----	Can be painted over after curing
BOSS® 352	Acrylic	White	5-10 mins	----	----	----	Can be painted over after curing

POLYURETHANE FOAM

Product Name	Base	Colour	Temp Resistance	Cutting time	Skin Formation Time	Remark	
BOSS® 333	Polyurethane	Champagne	-40°C to +90°C	30 mins	8 mins	High insulation value: thermal and acoustic	
BOSS® 334	Polyurethane	Champagne	-40°C to +90°C	30 mins	7 mins	High insulation value: thermal and acoustic	
BOSS® 813+	Polyurethane	Pink	-40°C to +90°C	50 mins	9.5 mins	Fire resistant in a joint (EN 1366-4)	

BATHROOM & SANITARY

SEALANTS							
Product Name	Base	Colour	Skin Formation Time	Tensile Strength	Elongation at Break	Shore A Hardness	Remark
BOSS® 395AF	Silicone	Available in multiple colours	10-15 mins	1.6-2.2 N/mm²	>700%	30	FDA certified food grade material, antifungal

GENERAL GLAZING APPLICATIONS

SEALANTS							
Product Name	Base	Colour	Skin Formation Time	Tensile Strength	Elongation at Break	Shore A Hardness	Remark
BOSS® 388	Silicone	Black, white, light brown, clear, brown, bronze	3-15 mins	0.8-1.2 N/mm²	>350	28-40	UV resistant
BOSS® 389+	Silicone	Clear, black, white, grey, light grey, brown, light brown	10-30 mins	1.5-2 N/mm²	>300	25-32	Long open time

CRACK FILLER

ACRYLIC FILLER							
Product Name	Base	Colour	Skin Formation Time	Temp Resistance	Application Temperature	Maximum Allowed Distortion	Remark
BOSS® No More Cracks	Acrylic	White	20 mins	-20°C to +80°C	5°C to +30°C	12%	Colourfast and waterproof after curing

CONSTRUCTION JOINTS

SAUSAGE							
Product Name	Base	Colour	Skin Formation Time	Temp Resistance	Application Temperature	Maximum Allowed Distortion	Remark
BOSS® PU Construction	Polyurethane	White & grey	20-40 mins	-30°C to +90°C	5°C to +40°C	±25%	High quality, elastic
BOSS® 235	SMX hybrid polymer	White, black, grey & other colours on request	25 min	-40°C to +90°C	5°C to +35°C	± 20 %	Strong elastic bonding in vibrating constructions



Accumetric Silicones Pvt. Ltd.

No. 16/1, Corporation Road, Seevaram, Perungudi,
Chennai - 600096, Tamil Nadu, India
For customer support: Tel.: +91 44 40 260345 - 60
indiasales@bossproducts.com

www.bossproducts.in

Authorised Dealer



CONSTRUCTION
CATALOGUE



www.bossproducts.in

ABOUT US

Our adhesives and sealing solutions are in high demand within a diverse range of industries. This is a testament to our consistent growth and success, as well as the superiority of our product range, unwavering commitment to quality, and expert project execution. Our solutions can be found in an ever-expanding array of finished products, solidifying our position as a trusted provider in the market.

BOSS 395AF

ANTI-FUNGAL BATHROOM & KITCHEN SEALANT



SEALING, SANITIZING, PROTECTING KITCHEN AND BATHROOM FITTINGS JOINTS FROM MOULD, MILDEW & FUNGUS



CRACK FILLER

BOSS® No More Cracks is a plasto-elastic joint and filling sealant based on acrylic dispersions. It offers a flexible, weather-resistant filling for interior and exterior surfaces and bonds well with various building materials. Ideal for sealing and filling cracks.



BATHROOM & SANITARY

BOSS® 395AF is a neutral antifungal silicone sealant that cures into a flexible elastomeric sealant when exposed to moisture in the air. It is versatile and suitable for various construction and glazing applications. Its excellent adhesion to non-porous substrates such as glass, ceramic tiles, and aluminum makes it easy to apply. Moreover, it can withstand temperature extremes, ozone, and ultraviolet radiation.



DOOR APPLICATIONS

BOSS® 334 is a one-component, minimal-expanding gun foam specially designed for sealing gaps around windows and doors. Its polyurethane formula expands upon contact with air to create an efficient seal that does not distort or bow window and door frames. The foam is ready-to-use and effective for sealing rough openings. Its unique properties make it an ideal choice for sealing windows and doors. Identical application products: Boss 333, 813+, 386 & 352.



WINDOW APPLICATIONS

BOSS® 333 is a versatile polyurethane foam that expands significantly upon contact with air. It's a great option for filling holes, cracks, and gaps, as it expands. Additionally, it offers excellent thermal & acoustic insulation and adheres well to most building materials. Identical application products: Boss 396, 354, 386.



CONSTRUCTION JOINTS

BOSS® PU Construction is a fast-curing, one-component, polyurethane adhesive sealant that cures upon exposure to moisture. Once cured, it forms a flexible, durable, and resilient elastomeric seal. The sealant has excellent adhesion to most industrial materials, making it ideal for construction and Building materials. Identical application products: Boss 235.



GENERAL GLAZING APPLICATIONS

BOSS® 388 is a one-part, neutral cure silicone sealant that provides superior adhesion and weather-resistance. Its low-odour formula makes it ideal for construction-grade applications. The sealant is compatible with a wide range of materials, making it versatile for various sealing and bonding needs. Identical application products: Boss 389+.

