



BOSS[®] C20-Cleaner

TECHNICAL DATA

Density	0.80 g/cm ³
Solids content	1 % maximum
Composition	Adhesion enhancer in an alcohol solution
Appearance	Colourless to slightly amber liquid, low viscosity

* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates.

** This information relates to fully cured product.

Description

BOSS C20-Cleaner is an adhesion enhancer necessary in the preparation of the glass.

Application

The required quantity is very small and amounts to a few microns of wet product. Use a clean and dry cotton cloth, wet it with BOSS C20-Cleaner and pass it over the surface to be prepared leaving a thin film. Then clean it down with a dry clean cloth.

Drying time of the film

Immediately

Covering time:

Maximum 4 hours after wiping.

After 4 hours, apply again BOSS C20-Cleaner.

Storage

Shelf life is 9 months from manufacturing date, in its original un-opened container if stored between 5°C and 35°C maximum. BOSS C20-Cleaner is sensitive to air moisture: bottles have to be closed tightly immediately after use and must be used within 5 days maximum. Frequent opening of the bottle will cause a step-by-step deterioration of the adhesion promotion characteristics of the product.

The necessity to frequently re-open a bottle is an indication that a small size bottle from our range should be selected. Cleaner which has obviously thickened or changed in appearance after opening must not be used. Do not open bottle until use.

Packaging

BOSS C20-Cleaner is available in 10ml or 1 Liter metal bottles.

Remarks

- Shake the bottles well before use.
- Always keep the mouth of the bottle closed & tight, do not leave it open.
- Keep the material in original container for storage, do not change aluminum bottle.
- Take the cleaner out as and when needed in desired quantity.
- Do not put unused cleaner back in bottle.
- Keep it away from the fire/welding area. Do not smoke, do not drink, do not inhale.
- Use cleaner and give 2-3 minutes to dry it completely.
- Use primer and give 5-10 minutes to dry it completely.

Disclaimer: This technical data sheet replaces all previous versions. The directives contained within this documentation are the result of our experiments and experience, and have been submitted in good faith. Because of the diversity of the materials and substrates, in addition to the great number of possible applications that go beyond our control, we cannot accept any responsibility for the results obtained. Further, since the design, quality of the substrate, and processing conditions are beyond our control, no liability under this publication will be accepted. In every case, it's therefore recommended to carry out preliminary experiments. BOSS reserves the right to modify its products, without prior notice.

Accumetric Silicone Pvt Ltd

Plot No.17, CMDA's Industrial Area, Melrosapuram,
Sengundram Village, S.P.Koil Post,
Chengalpattu - 603 204.
Email: info@bossproducts.in
Website: www.bossproducts.in