



## BOSS<sup>®</sup> 2010 Surface Activator

### TECHNICAL DATA

Base	Solvent mixture with additives
Consistency	Liquid
Curing System	Physical drying
Density	ca. 0.79 g/ml
Application temperature	+5°C → +25°C

### Description

Boss 2010 Surface Activator is a degreaser and adhesion promoter.

### Properties

- Improves adhesion on non porous substrates of silicones, MS and SMX based sealants.
- Do not use in combination with PU sealants.
- Suitable for powder-coated and anodised aluminum profiles.
- Ready to use and very user-friendly.
- Fast drying.
- Low consumption.

### Applications

- Improves adhesion
- Degreasing surfaces in sealant- or bonding applications.
- Improving the adhesion on powder coated aluminum (window profiles), both for regular as for textured powder coatings.
- Improving the adhesion on various plastics: PVC, ABS,...

### Packaging/Logistics

Colour: Please consult the product catalogue, the Boss website or a Boss representative.

Packaging: Please consult the product catalogue, the Boss website or a Boss representative.

Shelf life: 12 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C

### Substrates

Boss 2010 Surface Activator has a good adhesion to following substrates: non-porous substrates, powder coated aluminum. We recommend a preliminary adhesion and compatibility test on every surface.

### Application Method

Re-seal the packaging immediately after use of Boss 2010 Surface Activator. Long-term air contact reduces the working of Boss 2010 Surface Activator. Never pour back used remains of Boss 2010 Surface Activator into the packaging. Apply Boss 2010 Surface Activator with a cloth soaked in product. Always work with a clean cloth to avoid contamination of the surface. Replace if necessary. Always wipe in one direction. After cleaning the surface let dry sufficiently before applying the kit. The adhesive needs to be applied within 8 hours after application of Boss 2010 Surface Activator.

### Health and Safety Recommendations

Take the usual labour hygiene into account. Consult the packaging label and safety data sheet for more information. Dangerous. Respect the precautions for use.

### Remarks

- Due to the wide variety of possible plastics and paints and to avoid damage to the surface, a preliminary compatibility test is recommended.
- Do not use on porous surfaces like wooden constructions.

**Disclaimer:** This technical data sheet replaces all previous versions. The directives contained within this documentation are the result of our experiments and experience, and have been submitted in good faith. Because of the diversity of the materials and substrates, in addition to the great number of possible applications that go beyond our control, we cannot accept any responsibility for the results obtained. Further, since the design, quality of the substrate, and processing conditions are beyond our control, no liability under this publication will be accepted. In every case, it's therefore recommended to carry out preliminary experiments. BOSS reserves the right to modify its products, without prior notice.

### Accumetric Silicone Pvt Ltd

Plot No.17, CMDA's Industrial Area, Melrosapuram,  
Sengundram Village, S.P.Koil Post,  
Chengalpattu – 603 204.  
Email: info@bossproducts.in  
Website: www.bossproducts.in