

BOSS® CUT THE CRAP

TECHNICAL DATA

Base	Mixture based on natural solvents
Consistency	Aerosol
Density**	Ca. 0.85 g/ml
Application temperature	5 °C → 30 °C

* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. ** This information relates to fully cured product.

Description

BOSS® CUT THE CRAP is a non-aggressive mixture, based on natural solvents, suitable for removing fresh adhesive residues and most types of cured contact adhesive. Ideal for removing grease, oils and other dirt residues.

Properties

- Excellent cleaning properties
- Good degreasing properties
- Multi-purpose use
- Safe in use
- Non-corrosive
- Free of (aromatic) hydrocarbons

Applications

- Removes hard excess contact glue
- Suitable for removing fresh glue residues, oils, grease and other dirt residues

Packaging

Colour: Transparent

Packaging: 500 ml

Shelf life

2 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

Application method

Application method: Shake can well before use. Spray at a distance of appr. 20 cm of the object. Apply as

required. Leave to rest for a few minutes. After applying rub the surface dry with a clean towel. Always rub in one direction. Test for adverse effects on the surface in advance.

Health- and Safety Recommendations

Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water. Ingestion : rinse off the mouth with running water; avoid ingesting the liquid. Get in touch with a doctor. Consult label and material safety data sheet for more information.

Remarks

- Not suitable for polystyrene and PMMA.
- Greasy residue may remain, this can be removed with a degreaser.
- Cut the crap is not suitable to prepare the substrates for bonding. It is not a primer.
- Cut the crap can cause staining on porous surfaces.
- Due to the wide variety of possible plastics and paints and to avoid damage to the surface, a preliminary compatibility test is recommended.

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Disclaimer: This technical data sheet replaces all previous versions. The directives contained within this documentation are the result of our experiments and experience, and have been submitted in good faith. Because of the diversity of the materials and substrates, in addition to the great number of possible applications that go beyond our control, we cannot accept any responsibility for the results obtained. Further, since the design, quality of the substrate, and processing conditions are beyond our control, no liability under this publication will be accepted. In every case, it's therefore recommended to carry out preliminary experiments. BOSS reserves the right to modify its products, without prior notice.

Accumetric Silicones Pvt Ltd

No. 16/1, Corporation Road, Seevaram, Perungudi,
Chennai - 600 096, Tamil Nadu, India.
Customer Support: +91 44 4026 0345 - 60
indiasales@bossproducts.com
www.bossproducts.in