



## BOSS<sup>®</sup> P-20

### TECHNICAL DATA

Basis	Polyurethane
Consistency	Fluid
Curing System	Physical drying and reaction with moisture
Density	1.03 g/ml
Flashpoint	24 °C
Drying time (23°C and 50% R.H.)	Approx. 60 min (20°C/ 65% R.H.)
Consumption (*)	Ca. 5 m <sup>2</sup> /L
Application temperature	5 °C → 25 °C

\* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates.

\*\* This information relates to fully cured product.

### Product description

BOSS<sup>®</sup> P-20 is a universal primer based on polyurethane for porous substrates.

### Properties

- Liquid, easy application
- Suitable for all professional sealants based on polyurethane, polysulfide and MS Polymers

### Applications

- All porous surfaces
- Joint sides of expansion joints
- Joint sides of porous materials with raised water pressure

### Packaging

Colour: Transparent

Packaging: 500 ml aluminium tin

### Shelf life

12 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C. Protect against frost.

### Substrates

Substrates: All common porous building substrates  
Nature: Rigid, clean, dry, free of dust and grease.

### Application method

Recommendation : After application, minimum 1 hour and maximum 4 hours of waiting time before applying any joint sealant.

Application method: Apply with brush or roller in one full covering layer.

Cleaning: With White spirit immediately after use (not cured).

### Health and Safety Recommendations

Take the usual labour hygiene into account. Always wear gloves and goggles.

### Remarks

- If the maximum waiting time has passed before application, apply a new layer of BOSS<sup>®</sup> P-20.
- If the product is stored at higher temperatures (> 25°C), it is possible that the product becomes unusable before the due date.



## BOSS® P-20

### Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

### Users please read

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. The supplier warrants only that its products will meet its specifications. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. The user's exclusive remedy and the supplier's sole liability is limited to refund of the purchase price or replacement of any product shown to be otherwise than as warranted. The supplier will not be liable for incidental or consequential damages of any kind. Suggestions of uses should not be taken as inducements to infringe any patents.

**Disclaimer:** This technical data sheet replaces all previous versions. The directives contained within this documentation are the result of our experiments and experience, and have been submitted in good faith. Because of the diversity of the materials and substrates, in addition to the great number of possible applications that go beyond our control, we cannot accept any responsibility for the results obtained. Further, since the design, quality of the substrate, and processing conditions are beyond our control, no liability under this publication will be accepted. In every case, it's therefore recommended to carry out preliminary experiments. BOSS reserves the right to modify its products, without prior notice.

#### Accumetric Silicones Pvt Ltd

No. 16/1, Corporation Road, Seevaram, Perungudi,  
Chennai - 600 096, Tamil Nadu, India.  
Customer Support: +91 44 4026 0345 - 60  
indiasales@bossproducts.com  
www.bossproducts.in